

Variable frequency drive
Product overview

One source for engineering, manufacturing and support



EATON

Powering Business Worldwide

A drive for any application

Your application might call for an ultra-compact solution, clean power or future configurability.

Whether it is a standard product from the catalog or a custom-enclosed variable frequency drive (VFD) solution, Eaton delivers. Eaton drives are designed for industrial, HVAC, water/wastewater treatment, machinery OEM and other application demands.


Whether designing a new industrial complex, renovating an existing structure or developing a new machine, Eaton has the right product for your application.

Product selection matrix



Application	DC1	DA1	M-Max	H-Max	SVX	SPX	LCX	SPI/SPA	CPX	CFX
Single-phase input	Yes	Yes	Yes	—	Yes	Yes	—	—	—	—
Maximum 230V hp	5	7.5	15	125	125	125	—	—	200	100
Maximum 480V hp	15	15	25	250	250	2200	3200	2400	800	400
Maximum 575V hp	—	—	7.5	—	200	2300	2800	2200	800	400
Micro drive / MOEM	● ▲	● ▲	● ▲							
HVAC drive	● ▲			● ■						
General purpose					● ■	● ■				
High performance		● ▲				● ■	● ◆	● ◆	■	■
Harmonic mitigating									■	■

- = Standard open drive
- = Standard enclosed drive
- ▲ = Enclosed—consult Control Power Flex Center (Parma, OH)
- ◆ = Enclosed—consult Enclosed Drives Plant (Watertown, WI)

Drive	Applications	Description	Offering/Range	Benefits	Acceptance	Communication Options	Cross-Reference	Enclosure	
DC1 	<ul style="list-style-type: none"> General-purpose microdrive Machinery OEM drive 	The DC1 VFD is a compact VFD with only 14 basic parameters, SmartWire-DT connectivity and outstanding ease of mounting and installation. The DC1 is perfect for quick commissioning and is ideal for panel builders. This drive supports single-phase motor applications, and detachable terminal blocks make control wiring much easier.	Single-phase to single-phase 115V to 0.75 hp 230V to 1.5 hp Single-phase to three-phase 115V to 1.5 hp 230V to 5 hp	Three-phase to three-phase 230V to 5 hp 480V to 15 hp	Ease of use: Only 14 standard parameters for startup—quick commissioning, parameter copy function from drive to drive and PC connectivity via COM-STICK, integrated info card Space-saving design: DIN rail mountable, side-by-side mounting, contactor style wiring Efficiency: Temperature controlled fan Rugged and reliable: Ambient temperature –10°C to +50°C without any derating, high protection degree classes: IP66 for decentralized applications		<ul style="list-style-type: none"> Modbus RTU CANopen® SmartWire™ 	<ul style="list-style-type: none"> ABB (ACS 150, 355, 550) Danfoss (Micro Drive, VLT 2800) Hitachi (WJ200) Yaskawa (J1000, V1000) Lenze (SMD, 8400 BaseLine/StateLine) Siemens (Micromaster 420, G110, Sinamics G120C) WEG (CFW-10, CFW-08, CFW-09) 	<ul style="list-style-type: none"> Open IP20, IP66
DA1 	<ul style="list-style-type: none"> High-performance microdrive Machinery OEM drive 	The DA1 VFD is the perfect match for demanding OEM applications. High-performance processor, safe torque off, multiple fieldbus protocols including SmartWire-DT, sensorless vector control and the possibility to operate permanent magnet motors are sure to leave a lasting impression. In addition, detachable terminal blocks make control wiring much easier.	Single-phase to three-phase 230V to 3 hp	Three-phase to three-phase 230V to 7.5 hp 480V to 15 hp	Ease of use: Only 14 standard parameters for startup—quick commissioning, parameter copy function from drive to drive and PC connectivity via COM-STICK, integrated info card Space-saving design: DIN rail mountable, side-by-side mounting, contactor style wiring Efficiency: Temperature controlled fan Rugged and reliable: Ambient temperature –10°C to +50°C without any derating, high protection degree classes: IP66 for decentralized applications, STO, standard brake chopper circuit and RFI		<ul style="list-style-type: none"> DC1 Communications+ BACnet/IP® PROFIBUS DP DeviceNet EtherNet/IP 	<ul style="list-style-type: none"> ABB (ACS 150, 355, 550) Danfoss (Micro Drive, VLT 2800) Yaskawa (J1000, V1000) Schneider (ATV 312, 32) Siemens (Micromaster 420, G110, Sinamics G120C) Rockwell/Allen-Bradley (PowerFlex Series 4, 40) 	<ul style="list-style-type: none"> Open IP20, IP66
M-Max 	<ul style="list-style-type: none"> General-purpose microdrive 	The M-Max™ VFD is a compact microdrive with a broad power range, perfectly suited for machinery applications in many industries: food and beverage, HVAC, packaging, pumping, general machine and more.	Single-phase to three-phase 115V to 1.5 hp 230V to 3 hp	Three-phase to three-phase 230V to 15 hp 480V to 25 hp 575V to 7.5 hp	Ease of use: Startup Wizard, copy/paste tool, local/remote button, programmable multi-function inputs Space-saving design: DIN rail mountable, side-by-side mounting, numerous orientations, small footprint Efficiency: Average 30% less loss wattage, temperature controlled fan Rugged and reliable: High overload rating (CT), conformal coated circuit boards, NEMA® 1 enclosure option, EMC filters, brake chopper circuit, 50°C rating, temperature controlled fan		<ul style="list-style-type: none"> Modbus RTU PROFIBUS DP DeviceNet 	<ul style="list-style-type: none"> ABB (ACS Series 150, 155) Danfoss (VLT Micro Drive) Lenze/AC Tech (SC Series, SM Series) Rockwell/Allen-Bradley (PowerFlex Series 4, 40) Schneider/Square D (Altivar® Series 12, 312) Siemens (Micromaster 420) 	<ul style="list-style-type: none"> Open IP20, IP21 Open NEMA 1
H-Max 	<ul style="list-style-type: none"> HVAC drive 	The H-Max™ VFD is specifically designed to meet the needs of the HVAC industry by offering leading HVAC software and hardware features. With an industry-leading energy efficiency algorithm, high short-circuit current rating and robust design, it offers customers increased efficiency, safety and reliability.	—	Three-phase to three-phase 230V to 125 hp 480V to 250 hp	Ease of use: Startup Wizard, graphic display and keypad, menu-based navigation, copy/paste tool, local/remote button, programmable multi-function I/O, built-in communication protocols (BACnet, Modbus®, N2) Space-saving design: Compact design, open NEMA 12 option, onboard I/O expansion provisions Efficiency: “Active Energy Control,” offering 2–10% energy savings over competition Rugged and reliable: 5% DC choke with MOV protection, conformal coated circuit boards, EMC filters		<ul style="list-style-type: none"> Modbus RTU/TCP BACnet MS/IP LonWorks® 	<ul style="list-style-type: none"> ABB (ACH550) Danfoss (FC-102) Yaskawa (E7) Siemens (BT300) Vacon (100 HVAC) 	<ul style="list-style-type: none"> Open IP21, IP54 Open NEMA 1, 12 Enclosed NEMA 1, 12, 3R IntelliDisconnect (breaker included) IntelliPass (bypass included)
SVX 	<ul style="list-style-type: none"> General-purpose drive 	The SVX VFD is a general purpose, compact, modular solution for variable speed applications and offers a variety of features and application capabilities.	Single-phase to three-phase 230V to 40 hp 480V to 60 hp	Three-phase to three-phase 230V to 125 hp 480V to 250 hp 575V to 200 hp	Ease of use: Startup Wizard, seven built-in applications, local/remote button, modular design, text display Space-saving design: Compact design, open NEMA 12 option, onboard I/O expansion provisions Efficiency: Built-in 3% line reactor and EMI RFI filter H standard Rugged and reliable: High overload (CT) and low overload (VT) rated, robust time-proven design, durable metal power section, brake chopper circuit		<ul style="list-style-type: none"> EtherNet/IP Modbus RTU/TCP PROFIBUS DP DeviceNet CANopen LonWorks 	<ul style="list-style-type: none"> ABB (ACS310, ACS550) GE (AF-650) Rockwell/Allen-Bradley (PowerFlex 70, 753) Schneider/Square D (Altivar 61, 71) Siemens (Micromaster 430, Sinamics G120) Vacon (NXL) Yaskawa (P1000, A1000) 	<ul style="list-style-type: none"> Open IP21, IP54 Open NEMA 1, 12 Enclosed NEMA 1, 12, 3R AGSVX (agriculture config) Pump panel (pump config) Consult Eaton for NEMA 4X
SPX 	<ul style="list-style-type: none"> High-performance drive 	In applications where reliability and quality are essential for high performance, the SPX VFD is the ideal choice. They are equipped with high processing power, capable of closed loop feedback, safe torque off, permanent magnet motor operation, and very precise motor control.	—	Three-phase to three-phase 230V to 100 hp 480V to 2200 hp 575V to 2300 hp	Ease of use: Startup Wizard, seven built-in applications, customizable software, advanced capabilities and inputs, local/remote button, modular design, text display Space-saving design: Compact design, open NEMA 12 option, onboard I/O expansion provisions Efficiency: Built-in 3% line reactor and EMI RFI filter H standard, increased microprocessing power Rugged and reliable: High overload (CT) and low overload (VT) rated, robust time-proven design, durable metal power section, brake chopper circuit		<ul style="list-style-type: none"> EtherNet/IP Modbus RTU/TCP PROFIBUS DP DeviceNet CANopen LonWorks 	<ul style="list-style-type: none"> ABB (ACS800) Rockwell/Allen-Bradley (PowerFlex 700, 755) Schneider/Square D (Altivar 71) Siemens (Micromaster 440, Sinamics G130, G180, S120) Vacon (NXS) Yaskawa (A1000) 	<ul style="list-style-type: none"> Open IP20, IP21, IP54 Open NEMA 1, 12 Enclosed NEMA 1, 12, 3R Consult Eaton for NEMA 4X
LCX 	<ul style="list-style-type: none"> Liquid cooled drive 	The LCX VFD is well suited for locations when air-cooling would be difficult or expensive or when space is at a premium. These extremely compact drives are suitable for ships, mines and heavy industry.	—	Three-phase to three-phase 480V to 3200 hp 575V to 2800 hp	Ease of use: Startup Wizard, customizable software, advanced capabilities and inputs, local/remote button, modular design, text display Space-saving design: Compact space-saving design especially beneficial for NEMA 4X applications Efficiency: Advanced low heat transfer cooling system, increased microprocessing power Rugged and reliable: Same reliable control module and operating system as SPX		<ul style="list-style-type: none"> EtherNet/IP Modbus RTU/TCP PROFIBUS DP DeviceNet CANopen LonWorks 	<ul style="list-style-type: none"> ABB (ACS8000-07LC) Rockwell/Allen-Bradley (PowerFlex 700L) Schneider/Square D (Altivar 61Q) Siemens (Sinamics G150) Vacon (NXP) 	<ul style="list-style-type: none"> Open IP00
SPI/SPA 	<ul style="list-style-type: none"> Common DC bus drive Active front end drive Regenerative drive 	Eaton offers a comprehensive range of common DC bus VFD products. This includes a number of front-end units and inverter units in the entire power range. Common DC bus drives are used in a multitude of applications and combinations. Drives that are braking can transfer the energy directly to the drives in a motoring mode.	—	Three-phase to three-phase 480V to 2400 hp 575V to 2200 hp	Ease of use: Startup Wizard, customizable software, advanced capabilities and inputs, local/remote button, modular design, text display Space-saving design: Compact modular expandable design Efficiency: Bidirectional/regenerative energy savings capabilities Rugged and reliable: Same reliable control module and operating system as SPX, shared components for inverter and active front end for reduced spare		<ul style="list-style-type: none"> EtherNet/IP Modbus RTU/TCP PROFIBUS DP DeviceNet CANopen LonWorks 	<ul style="list-style-type: none"> ABB (ACS8000-U11) Emerson (Unidrive SP) Rockwell/Allen-Bradley (PowerFlex 20, 700AFE) Schneider/Square D (Altivar ATV32, LXM32) Siemens (Sinamics S120) Vacon (NXP) Yaskawa (F7) 	<ul style="list-style-type: none"> Open IP00, IP21 Open NEMA 1
CPX 	<ul style="list-style-type: none"> 18-pulse drive 	The CPX VFD uses advanced 18-pulse clean power technology that significantly reduces line harmonics at the drive input terminals and is designed to exceed IEEE 519-1992 requirements. Delivering true power factor and reducing harmonic distortion prevents upstream transformer overheating and overloading of breakers and feeders, enabling the application of variable frequency drives on generators and other high-impedance power systems.	—	Three-phase to three-phase 230V to 200 hp 480V to 800 hp 575V to 800 hp (Consult Eaton for larger hp)	Ease of use: Uses the core SVX/SPX drive platform; therefore, sharing many of the drive-related characteristics of the component drive including Startup Wizard and built-in applications Space-saving design: Designed and engineered to optimize space, including flange mounting the drive with the heat sink external to the enclosure. Smallest footprint in the industry Efficiency: Designed and tested to provide maximum efficiency through best-in-class components Rugged and reliable: Proven design built on 10+ years of experience in 18-pulse engineering		<ul style="list-style-type: none"> EtherNet/IP Modbus RTU/TCP PROFIBUS DP DeviceNet CANopen LonWorks 	<ul style="list-style-type: none"> ABB Rockwell/Allen-Bradley Schneider/Square D Yaskawa 	<ul style="list-style-type: none"> Enclosed NEMA 1, 12 and 3R Consult Eaton for NEMA 4X
CFX 	<ul style="list-style-type: none"> Filtered drive 	The CFX VFD uses a tuned passive filter to significantly reduce the line harmonics generated by a standard 6-pulse drive. Designed for small to mid-sized drive applications, the CFX, in conjunction with the CPX, offers the user a tiered approach to harmonic mitigation.	—	Three-phase to three-phase 230V to 100 hp 480V to 400 hp 575V to 400 hp	Ease of use: Uses the core SVX/SPX drive platform, Startup Wizard, built-in applications Space-saving design: Designed and engineered to optimize space including flange mounting the drive with the heat sink external to the enclosure. Smallest footprint in the industry Efficiency: Designed and tested to provide maximum efficiency through best-in-class components Rugged and reliable: Tested and proven solution built to meeting commercial and industrial applications. Engineered solutions to further protect filter and drive available		<ul style="list-style-type: none"> EtherNet/IP Modbus RTU/TCP PROFIBUS DP DeviceNet CANopen LonWorks 	<ul style="list-style-type: none"> ABB Rockwell/Allen-Bradley Schneider/Square D Yaskawa 	<ul style="list-style-type: none"> Enclosed NEMA 1, 12 and 3R Consult Eaton for NEMA 4X
SC 9000 	<ul style="list-style-type: none"> Medium voltage drive 	The Ampgard® SC 9000™ medium voltage VFD combines innovative technology with the reliable design and construction of Eaton Ampgard products. Designed for use with induction or synchronous motors, the Ampgard SC 9000 delivers maximum benefits while being the smallest medium voltage drive in the industry.	—	Three-phase to three-phase 2400 to 4160V Up to 6000 hp	Ease of use: Drive can be integrated into Ampgard motor control products lineup connected by common bus, common control board and keypad with low voltage product offering Space-saving design: Smallest footprint in the industry, common bus connection to other motor control products for ease of installation Efficiency: Integrated 24-pulse converter, three-level inverter topology Rugged and reliable: Full load burn-in testing completed on every drive, time-proven Ampgard motor control assembly design, encapsulated drawout inverted to reduce risk of environmental contamination		<ul style="list-style-type: none"> EtherNet/IP Modbus RTU/TCP PROFIBUS DP DeviceNet CANopen LonWorks 	<ul style="list-style-type: none"> Siemens (ROBICON Perfect Harmony™) Rockwell/Allen-Bradley (PowerFlex 7000) Toshiba (T300MVi) ABB (ACS 1000) 	<ul style="list-style-type: none"> Enclosed NEMA 1

Selection considerations

- What is your system application?
- Is your load constant torque or variable torque?
- What are your voltage and hp requirements?
- What is the motor Full Load Amps (FLA)?
- Do you need an open or enclosed product?
- What NEMA enclosure rating do you need?
- Do you need a main breaker or a bypass?
- Do you need any accessories or communication cards?

Key contacts

Contact	Phone	Email
Technical support	(877) 386-2273 x2 x6 x3	TRCDrivesTechSupport@Eaton.com
Pre-sale support	(877) 386-2273 x2 x6 x2	PreSaleVFD@Eaton.com
Post-sale support	(877) 386-2273 x2 x6 x3	VFDAftermarketEG@Eaton.com

Online resources

Resource	Website
Eaton drives	Eaton.com/Drives
Eaton engineer services	Eaton.com/EESS
Eaton systems integrators	Eaton.com/SI
Eaton CAD drawings	Eaton.com/Drawings
Eaton software downloads	Eaton.com/Software
Eaton Europe	Eaton.eu/Electrical
Eaton Asia	Eaton.com.cn

Warranty process

Required information: product serial number, original general order number, customer site location, contact information and detailed description of the issue.

1. Call Post-Sale Support for troubleshooting assistance at (877) 386-2273 x2 x6 x3.
2. Contact EatonCare or CORE for warranty parts and service processing at (877) 386-2273 x4 x2.
3. Return replaced components per the instructions provided on the return paperwork.

PC software

Software

9000XDrive and 9000XLoad—Used with SVX, SPX, LCX, SPI, SPA and all enclosed drives using these units

MaxConnect and MaxLoader—Used with M-Max and H-Max

DrivesConnect—Used with DA1 and DC1

Notes:

Download at Eaton.com/software → Adjustable Frequency Drives.

Download at Eaton.com/drives → Software Downloads.

Online training

Eaton 101 Series—Low Voltage Motor Control

<http://www.eaton.com/Eaton/ProductsServices/Electrical/Support/Training/101BasicsSeries/index.html>

M-Max VFD Demo Simulator—Online M-Max Demo Simulation

Online M-Max training simulator that reviews the keypad, display, menu navigation, basic parameter changes and the operation of the demo cases (www.eaton.com/m-maxdemo)

Classroom training

Certification and Service Training

Commissioner Certification Training (SVX, SPX, H-Max, CPX, CFX)

Service Provider Training (SVX, SPX, CPX, CFX, HVX)

Note:

Eaton.com/drives → Aftermarket → Training and Tools.

Calculators

Harmonics Estimator—Estimate Total Harmonic Distortion (THD) of System

By having the transformer information and the one-line diagrams, a harmonics analysis can be quickly put together to ensure the system will meet requirements set by IEEE 519. Drive configurations can quickly be changed, allowing engineers to provide the most cost-effective solution (www.eaton.com/drives → Software Downloads → Register for Harmonics Calculator)

Energy Savings Estimator—Estimate ROI for System

The program creates an Energy Savings Estimation Report that details yearly energy savings, reduction in CO₂ emissions and estimated payback time by analyzing system configuration, total installation costs and duty cycle (www.eaton.com/drives → Software Downloads → Register for Energy Savings Estimator)

Continue to learn more about Eaton drives, enclosed VFD offering and services.

Please visit us at Eaton.com/drives



Eaton
1000 Eaton Boulevard
Cleveland, OH 44122
United States
Eaton.com

© 2013 Eaton
All Rights Reserved
Printed in USA
Publication No. BR040002EN / Z14462
November 2013



Powering Business Worldwide

Eaton is a registered trademark.

All other trademarks are property of their respective owners.